

RIDGE

METAL ROLL

FLEXIBLE VENTILATED ALUMINIUM UNDER-RIDGE

EXCELLENT ADHESION

The special 4 cm wide butyl tape ensures strong and immediate adhesion to various surfaces.

DURABILITY

The choice of metal material ensures excellent UV stability even in harsh climate zones.



TECHNICAL DATA

Properties	value	USC conversion
Material	aluminium, butyl	-
Butyl tape width	40 mm	1.57 in
Butyl tape adhesion property	> 19 N/cm	1.68 lb/in
UV resistance	permanent	-
Application temperature	+5 / +30 °C	+41 / +86 °F
Temperature resistance	-30 / +90 °C	-22 / +194 °F
Storage temperature ⁽¹⁾	0 / +25 °C	+32 / +77 °F

⁽¹⁾ Keep the product in a dry, covered location.
Waste classification (2014/955/EU): 17 09 04.

CODES AND DIMENSIONS

CODE	B	L	B	L	colour	RAL	
	[mm]	[m]	[in]	[ft]			
METRED400	400	5	15.8	16	brick red	8004	4
METBRO400	400	5	15.8	16	brown	8017	4
METANT400	400	5	15.8	16	anthracite	7021	4

RECOMMENDATIONS FOR INSTALLATION

