

BONDING GLUE

HIGH ELASTICITY UNIVERSAL ADHESIVE GLUE FOR EXTERNAL USE

- Also for outdoor use, it provides excellent water resistance
- Glue for membranes and sealant for joints
- Very high adhesion on the most common building materials



BUTYL BASED

CODE	content	version	yield with glue line Ø8 mm	pcs
BONGLU600	600 ml - 840 g	soft cartridge	approx. 6 m	12



INSTRUCTIONS FOR USE

Allow the product to warm up to room temperature before use (do not heat with heaters). The surfaces of the parts to be glued must be dry and free of dust and grease.

Apply an adhesive strip with a minimum diameter of 5 mm (possibly more in case of rough substrates) on the film, on the window joint tape or on the substrate material. Then apply the film or window joint tape without excessively pressing the adhesive so that the movements of the structure can be easily absorbed.

Remove uncured glue from work tools with water.

WARNINGS

- Dispose of contents/container in accordance with local regulations
- Follow the information on the safety data sheet

TECHNICAL DATA

properties	value
composition	butyl rubber
colour	grey
density	1,39 g/mL
film formation time 20 °C / 50% RH ⁽¹⁾	20 - 30 min
time required for complete hardening 20 °C / 50% RH ⁽¹⁾	4 - 6 weeks
temperature resistance once hardened	-25 / +70 °C
Shore A hardness	approx. 15
application temperature (cartridge, environment and support)	+5 / +40 °C
watertightness after hardening	conforming
transport temperature	+5 / +30 °C
storage temperature ⁽²⁾	+5 / +25 °C

⁽¹⁾The data expressed may vary depending on the thickness of the product applied and the specific installation conditions: temperature, humidity, ventilation, absorbency of the substrate.

⁽²⁾The product remains stable for 12 months if stored in the original packaging in a dry and covered place. Check the expiry date on the packaging.

EUH066 Repeated exposure may cause skin dryness or cracking. EUH210 Safety data sheet available on request.