AIR BITUM

BITUMINOUS MEMBRANE SEALANT SPRAY, READY FOR USE

- · Waterproofs and seals providing weather resistance
- It is effective on all types of support and shapes
- Ideal for sealing infiltrations on roofs, gutters, pipes and more
- The special elastomer-modified bituminous formula guarantees a product that after drying resists both weathering and salt corrosion







				BITOMEN BASED
CODE	content	colour	yield	pcs
	[mL]			
AIRBIT500	500	black	approx. 4 m ²	12



INSTRUCTIONS FOR USE

It is always advisable to have the correct Personal Protective Equipment (PPE) and to consult the technical data sheet and safety data sheet before starting the supply.

Thoroughly clean surfaces and ensure that any loose or crumbling parts, paint, rust or dust are removed. Shake the can well until you feel the steel ball move inside the can. Spray intermittently to obtain and maintain an even spray pattern. Drying times of the product depend on the thickness of the applied layer, the type of surface and environmental conditions. When application is complete, turn the can upside down and spray for 1-2 seconds so the nozzle stays clean and does not get clogged.

WARNINGS

- Do not use in areas without ventilation
- Flammable product
- Do not breathe vapours/aerosols
- Avoid contact with eyes and skin
- Keep out of reach of children
- Dispose of contents/container in accordance with local regulations
- Follow the information on the safety data sheet
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use

TECHNICAL DATA

properties	value
time required for complete drying 23 °C / 50% $\rm RH^{(1)}$	1 - 4 h
application temperature	+5 / +35 °C
storage temperature ⁽²⁾	+10 / +30 °C

⁽¹⁾The data expressed may vary depending on the thickness of the product applied and the specific installation conditions: temperature, humidity, ventilation, absorbency of the substrate.

Aerosol 1. Skin Irrit. 2. STOT SE 3. Aquatic Chronic 2



The product remains stable for 24 months if stored in the original packaging in a dry and covered place. Check the expiry date on the packaging.