

# FIRE STRIPE



## INTUMESCENT THERMO-INFLATABLE FLEXIBLE GASKET

### INTUMESCENT

It expands under the effect of strong heat. As it expands, it seals the cavity in which it is placed, blocking the passage of flames.

### FIRE PROTECTION

Installable in tight spaces, it is perfect for the fire protection of our concealed fastening systems.




## TECHNICAL DATA

Properties	standard	value	USC conversion
Colour	-	grey	-
Reaction to fire	EN 13501-1 NF P92-501	B-s3, d0 M1 - non-flammable	- -
Application temperature	-	+5 / +35 °C	+41 / +95 °F
Storage temperature	-	+1 / +25 °C	+33.8 / +77 °F
French VOC classification	ISO 16000	A+	-

<sup>(1)</sup> Store the product in a cool, dry place for no more than 12 months.  
Waste classification (2014/955/EU): 08 04 10.

## CODES AND DIMENSIONS

CODE	B	s	L	B	s	L	
	[mm]	[mm]	[m]	[in]	[mil]	[ft]	
FIRESTRIFE10	10	2	6	0.4	79	20	56



### DURABILITY

The profile has good resistance to UV and thermal stress and is not subject to rotting.

### FAST INSTALLATION

The tape is adhesive, is installed quickly and no support tools are required.