

BUTYL BAND

DOUBLE-SIDED UNIVERSAL BUTYL TAPE



STRONG

The polyester grid guarantees consistence and high resistance.

HERMETIC

Appropriate for watertight seals for timber-to-timber and/or timber-to-concrete joints.



TECHNICAL DATA

Properties	standard	value	USC conversion
Maximum tensile force MD/CD	EN 12311-1	115 / 140 N/50 mm	13.13 / 16 lbf/in
Elongation at break point MD/CD	EN 12311-1	15 / 15%	-
Adhesion on steel at 180°	ASTM D 1000	35 N/cm	20 lbf/in
Initial Tack	ASTM D 2979	10 N	2.25 lbf
Reaction to fire	EN 13501-1	class E	-
Temperature resistance	-	-30 / +130 °C	-22 / +266 °F
Application temperature	-	+5 / +40 °C	+41 / +104 °F
Storage temperature ⁽¹⁾	-	+5 / +40 °C	+41 / +104 °F
Solvents	-	no	-
VOC emissions	ISO 16000	30 µg/m ³	-
French VOC classification	ISO 16000	A+	-

⁽¹⁾Store the product in a cool, dry place for no more than 12 months.
Waste classification (2014/955/EU): 08 04 10.

CODES AND DIMENSIONS

CODE	B	s	L	B	s	L	
	[mm]	[mm]	[m]	[in]	[mil]	[ft]	
BUTYLBAND1501	15	1	15	0.6	39	49	20
BUTYLBAND1502	15	2	10	0.6	79	33	13



SPECIAL BUTYL MIX

Thanks to its special modified butyl formulation, it ensures excellent durability even when subjected to thermal stress and UV radiation.

ADJUSTABLE

Butyl is also perfectly suited for installation in tight spaces and on irregular profiles without resistance.