

AIR GLUE



FAST DRYING UNIVERSAL SPRAY GLUE

- Contact adhesive for timber, metal, rubber, vinyl, plastic, cardboard, concrete and other materials
- Improves the adhesion of acrylic tapes to materials such as concrete and fibrous insulation layers
- It can be used both indoors and outdoors
- Adjustable spray width



CODE	content [ml]	pcs
AIRGLUE750	750	12



INSTRUCTIONS FOR USE

It is always advisable to have the correct Personal Protective Equipment (PPE) and to consult the technical data sheet and safety data sheet before starting the supply. Thoroughly clean surfaces and ensure that any loose or crumbling parts, paint, rust or dust are removed. Shake the can well before dispensing and rotate the nozzle to increase or decrease the spray size. Spray evenly over the surface, repeat the process for highly absorbent surfaces. Protect the adhesive surface from dust and moisture during the drying process. The surface is ready for bonding when it is dry to the touch and the glue does not transfer. To use the glue as a contact adhesive distribute it on both surfaces.

WARNINGS

- Do not use in areas without ventilation
- Flammable product
- Do not breathe vapours/aerosols
- Avoid contact with eyes and skin
- Keep out of reach of children
- Dispose of contents/container in accordance with local regulations
- Follow the information on the safety data sheet
- Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use

TECHNICAL DATA

properties	value
composition	mix of thermoplastic adhesive and solvent
time required for drying 20 °C / 50 % RH ⁽¹⁾	1 - 2 min
application temperature (spray can, support and environment)	+15/+25°C
temperature resistance once dried	-10/+100°C
French VOC classification	A+
transport temperature	+5/+50°C
storage temperature ⁽¹⁾	+15/+35 °C

⁽¹⁾Store the product in a dry place and check the date of manufacture on the cartridge.

Waste classification (2014/955/EU): 16 05 04.

Aerosol 1 - H222, H229.