

AIR BITUM

BITUMINOUS MEMBRANE SEALANT SPRAY, READY FOR USE

- Waterproofs and seals providing weather resistance
- It is effective on all types of support and shapes
- Ideal for sealing infiltrations on roofs, gutters, pipes and more
- The special elastomer-modified bituminous formula ensures a product that after drying resists both weathering and salt corrosion



RESISTANT TO
MOISTURE



SPRAY



READY FOR
USE



BITUMINOUS

CODE	content [ml]	colour	yield	pcs
AIRBIT500	500	black	approx. 4 m ²	12

INSTRUCTIONS FOR USE

It is always advisable to have the correct Personal Protective Equipment (PPE) and to consult the technical data sheet and safety data sheet before starting the supply.

Thoroughly clean surfaces and ensure that any loose or crumbling parts, paint, rust or dust are removed. Shake the can well until you feel the steel ball move inside the can. Spray intermittently to obtain and maintain an even spray pattern. Drying times of the product depend on the thickness of the applied layer, the type of surface and environmental conditions. When application is complete, turn the can upside down and spray for 1-2 seconds so the nozzle stays clean and does not get clogged.

WARNINGS

- Do not use in areas without ventilation
- Flammable product
- Do not breathe vapours/aerosols
- Avoid contact with eyes and skin
- Keep out of reach of children
- Dispose of contents/container in accordance with local regulations
- Follow the information on the safety data sheet
- Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use

TECHNICAL DATA

properties	value
time required for drying 23 °C / 50% RH ⁽¹⁾	1 - 2 h
temperature resistance after drying	-10/+60 °C
yield ⁽¹⁾	4 m ²
application temperature (cartridge, support and ambient) ⁽²⁾	+5/+35 °C
transport temperature	+5/+35 °C
storage temperature ⁽³⁾	+5/+30 °C
VOC	46 %/460 g/l

⁽¹⁾Average value that varies depending on the desired thickness of the layer.

⁽²⁾When application is complete, turn the can upside down and spray for 1-2 seconds so the nozzle stays clean.

⁽³⁾Store the product in a dry, covered location away from heat, open flames or other sources of ignition. Check the date of manufacturing on the packaging.

Waste classification (2014/955/EU): 16 05 04.

Aerosol 1. Skin Irrit. 2. STOT SE 3. Aquatic Chronic 2.