

INTERNA



SINGLE-SIDED TAPE FOR INDOOR USE

- The pre-formed carrier allows easy sealing of complex corners and edges
- It is also available with pre-cut liner for faster installation
- Reinforced paper support, ideal for indoor use; airtightness ensured over time



CODE	liner		B		L		pcs
	[mm]	[in]	[mm]	[in]	[m]	[ft]	
INTERNA60	60	2.4	60	2.4	25	82	10
INTERNA3030	30 / 30	1.2 / 1.2	60	2.4	25	82	10
INTERNA1248	12 / 48	0.5 / 1.9	60	2.4	25	82	10

Thickness: 0,33 mm

COMPOSITION:

- ① support: paper reinforced with protective film
- ② glue: acrylic dispersion without solvents
- ③ release liner: silicone paper



TECHNICAL DATA

properties	standard	value
thickness	EN 1942	0,3 mm
adhesion strength on steel at 90°	ISO 29862	≥ 35 N/25 mm
adhesion strength on OSB at 90° after 10 minutes	EN 29862	3,5 N/10 mm
adhesion strength on OSB at 180° after 10 minutes	EN 29862	11,0 N/10 mm
adhesion strength (average) on membrane in PP after 24 hours ⁽¹⁾	EN 12316-2	15,0 N/50 mm
shear adhesion strength of the joint on membrane in PP after 24 hours ⁽²⁾	EN 12317-2	120,0 N/50 mm
water vapour transmission (Sd)	EN ISO 12572	6 m
application temperature ⁽³⁾	-	0/+40 °C
resistance to temperature	-	-30/+100 °C
storage temperature ⁽⁴⁾	-	+15/+25 °C
French VOC classification	ISO 16000	A+
VOC emissions	EN 16516	very low
solvents	-	no

⁽¹⁾ Minimum required value according to DTU 31.2 P1-2 (France): 15 N/50 mm.

⁽²⁾ Minimum required value according to DTU 31.2 P1-2 (France): 40 N/50 mm.

⁽³⁾ On dry support and at a temperature > 0 °C. The absence of condensation or frost on the surface must be guaranteed.

⁽⁴⁾ Store the product in a cool, dry place for no more than 12 months.

♻️ Waste classification (2014/955/EU): 08 04 10.

SCREWS FOR TIMBER
 SCREWS AND FASTENERS FOR DECKS
 SCREWS FOR METAL
 PLATES AND ANGLE BRACKETS
 POST BASES AND FENCES
 ANCHORS AND CHEMICAL ANCHORS
 METRIC
 MEMBRANES
 SEALANTS, TAPES AND PROFILES
 WINDOW SEALING
 SOUNDPROOFING
 ROOF ELEMENTS
 TOOLS