

# SPRINTA



## UNIVERSAL SINGLE-SIDED TAPE WITHOUT RELEASE LINER

- It can be applied both indoors and outdoors, providing fast and secure sealing
- No separation film means less waste to dispose of, for greater environmental sustainability
- It can be easily torn off thanks to the serrated edges that facilitate cutting the tape without the use of scissors or cutters
- Speed installation and good adhesion strength on most common building materials



CODE	liner		B		L		pcs
	[mm]	[mm]	[in]	[m]	[ft]		
SPRINTA60	/	60	2.4	25	82	10	

Thickness: 0.25 mm

### COMPOSITION:

- ① support: PE film
- ② glue: solvent-free UV-crosslinked acrylic
- ③ reinforcing layer: polyester reinforcing grid
- ④ glue: solvent-free UV-crosslinked acrylic

## TECHNICAL DATA

properties	standard	value
thickness	AFERA 5006	0,25 mm
adhesion strength on OSB at 90° after 10 minutes	EN 29862	4,8 N/10 mm
adhesion strength on OSB at 180° after 10 minutes	EN 29862	11,0 N/10 mm
adhesion strength (average) on membrane in PP after 24 hours <sup>(1)</sup>	EN 12316-2	26,0 N/50 mm
shear adhesion strength of the joint on membrane in PP after 24 hours <sup>(2)</sup>	EN 12317-2	120 N/50 mm
adhesion strength on steel at 90°	AFERA 5001	≥ 25 N/25 mm
water vapour transmission (Sd)	EN 1931	40 m
exposure to weather	-	12 months
watertightness	-	compliant
resistance to temperature	-	-40/+80 °C
fire resistance rating on plain CLT joint (100 mm), 3 mm joint <sup>(*)</sup>	EN 1363-4	EI 90
application temperature <sup>(3)</sup>	-	-10/+ 40 °C
storage temperature <sup>(4)</sup>	-	+5/+30 °C
French VOC classification	ISO 16000	A+
solvents	-	no

<sup>(1)</sup>Minimum required value according to DTU 31.2 P1-2 (France): 15 N/50 mm.

<sup>(2)</sup>Minimum required value according to DTU 31.2 P1-2 (France): 40 N/50 mm.

<sup>(3)</sup>On dry support and at a temperature > 0 °C. The absence of condensation or frost on the surface must be guaranteed.

<sup>(4)</sup>Store the product in a cool, dry place for no more than 6 months.

<sup>(\*)</sup>For full details and tested configurations, please contact our technical department.

♻️ Waste classification (2014/955/EU): 08 04 10.



SCREWS FOR TIMBER  
 SCREWS AND FASTENERS FOR DECKS  
 SCREWS FOR METAL  
 PLATES AND ANGLE BRACKETS  
 POST BASES AND FENCES  
 ANCHORS AND CHEMICAL ANCHORS  
 METRIC  
 MEMBRANES  
 SEALANTS, TAPES AND PROFILES  
 WINDOW SEALING  
 SOUNDPROOFING  
 ROOF ELEMENTS  
 TOOLS