


SELF-EXPANDING SEALING TAPE FOR WINDOWS/DOORS

- It seals the joints of doors and windows from air and heavy rain while maintaining the thermal-acoustic properties over the entire depth
- For cracks between 6 and 15 mm. It adapts to the surface, ensuring air and water tightness by acting as a vapour control membrane
- Ensures a high level of thermal and acoustic insulation.



CODE	B		s				L		pcs
	[mm]	[in]	[mm]	[mm]	[mm]	[mm]	[m]	[ft]	
FENESTRA54615	54	2.1	6	15	236	591	15	49	7
FENESTRA74615	74	2.9	6	15	236	591	15	49	5

COMPOSITION:

elastic polyurethane foam with additives



TECHNICAL DATA

properties	standard	value
classification	DIN 18542	BG 1
airtightness	EN 12114	$\alpha \leq 1.0 \text{ m}^3/(\text{h}\cdot\text{m}\cdot(\text{daPa})^n)$
tightness in heavy rain	EN 1027	$\geq 600 \text{ Pa}$
resistance to UV and weathering	DIN 18542	compliant with class BG 1
compatibility with other building materials	DIN 18542	compliant with class BG 1
water vapour resistance factor (μ)	EN ISO 12572	< 100
vapour pressure gradient	-	externally permeable
reaction to fire	DIN 4102-1	class B1
acoustic insulation of the joint		59 dB
thermal conductivity (λ)	EN 12667	$\leq 0.043 \text{ W}/(\text{m}\cdot\text{K})$
thermal resistance	-	-30 / +90 °C
application temperature	-	$\geq +5 \text{ °C}$
storage temperature ⁽¹⁾	-	+1 / +20 °C

⁽¹⁾ Store the product in a cool, dry place for no more than 24 months.

Waste classification (2014/955/EU): 17 02 03.